



**material: ColoRex<sup>®</sup> SD/EC**

<b>physical properties:</b>	tile size . . . . .	24.2" x 24.2" approx. (61.5 cm x 61.5 cm)
	gauge . . . . .	0.080" (2.0 mm)
<b>recycled content:</b>	pre-consumer (post-industrial)* . . . . .	51.0%
materials & resources credit 4	post-consumer . . . . .	0%
1-2 points (NC, schools, CS, CI)		
<b>indoor environmental quality:</b>	collaborative for high performance schools low emitting materials section 01350	
low emitting materials (flooring systems) credit 4.3	Low Emitting Materials Table (LEM) . . . . .	listed
1 point (NC, schools, CS, CI) option 2		
<b>indoor environmental quality:</b>	adhesives meet the requirements set forth in	
low emitting materials (adhesives & sealants) credit 4.1	the SCAQMD Rule #1168 . . . . .	Forbo C-930
1 point (NC, schools, CS, CI)		
<b>regional materials:</b>	manufacturing	facility: Forbo Guibiasco SA
materials & resources credit 5		Guibiasco, Switzerland
1-2 points (NC, schools, CS, CI)		
<b>regional extraction/process:</b>	<b>ingredient</b>	<b>extraction location</b>
	PVC . . . . .	Germany
	plasticizer . . . . .	France
	titanium oxide (TiO2) . . . . .	Germany
	CaCO3 (calcium carbonate) . . . . .	Italy
	stabilizer . . . . .	Italy
	binder (chip coating) . . . . .	Germany
	masterbatch . . . . .	Italy
	lubrificants . . . . .	Italy
	conductive element . . . . .	Belgium

**material: Forbo Wall Base**

<b>physical properties:</b>	feet per carton. . . . .	4" wall base = 120 linear feet per carton
		6" wall base = 96 linear feet per carton
	gauge . . . . .	1/8"
	style . . . . .	cove or straight toe
<b>recycled content:</b>	pre-consumer (post-industrial)* . . . . .	32.0%
materials & resources credit 4	post-consumer . . . . .	0%
1-2 points (NC, schools, CS, CI)		
<b>indoor environmental quality:</b>	adhesives meet the requirements set forth in	
low emitting materials (adhesives & sealants) credit 4.1	the SCAQMD Rule #1168 . . . . .	Forbo Wall Base Adhesive
1 point (NC, schools, CS, CI)		
<b>regional materials:</b>	manufacturing . . . . .	facility: VPI Corporation
materials & resources credit 5		Sheboygan, WI
1-2 points (NC, schools, CS, CI)		
<b>regional extraction/process:</b>	<b>ingredient</b>	<b>extraction location</b>
	resin . . . . .	Mississippi, United States
	epoxidized soybean oil . . . . .	Minnesota, United States
	wax . . . . .	North Carolina, United States
	titanium oxide . . . . .	Michigan, United States
	thermoplastic rubber . . . . .	Mexico
	plasticizer . . . . .	Louisiana, United States
	stabilizer . . . . .	Indiana, United States
	clay . . . . .	Georgia, United States
	stearic acid . . . . .	Illinois, United States

\* recycled content calculated following Federal Trade Commission (FTC) –Part 260 - GUIDES FOR THE USE OF ENVIRONMENTAL MARKETING CLAIMS

\* recycled content materials shall be defined in accordance with the International Organization of Standards document, ISO 14021 - environmental labels and declarations - self-declared environmental claims (type II environmental)